



HIG-CD 3k6

- It is necessary to observe the use of the appropriate coupling unit for the specific insulation monitoring device.
- The coupling devices HIG-CD are used to adapt the input circuits of the insulation monitoring device to a higher operating voltage than the operating voltage of the IMD directly.
- The coupling devices are connected between the insulated system and the insulation monitoring device.

Type		HIG-CD 3k6
Rated operating AC voltage	U_N	2 500 V
Rated operating DC voltage	U_N	3 600 V
Maximum continuous operating voltage AC	U_C	2 500 V
Maximum continuous operating voltage DC	U_C	3 600 V
Designed for insulation monitoring device		HIG99/3k6
Use for traction		Yes
Housing material		Aluminium, Electroinsulating potting compound
Degree of protection		IP65, except for connecting wires
Operating temperature	ϑ	$-40 \div 70$ °C
Recommended cross-section of connected conductors	S	2.5 mm ²
Installation		On the mounting plate
Operating position		Any
Operation type		Permanent
Lifetime		> 100 000 h
Designed according to standards		
Adjustable speed electrical power drive systems – Safety requirements		IEC 61800-5-1:2007
Railway applications – Fire protection on railway vehicles		EN 45545-2:2013
Ordering, packaging and additional data		
Mass	m	135 g
Customs tariff no.		90303370
EAN code		8590681188903
Art. number		70 984



The link in the QR code leads to the online presentation of the **HIG-CD 3k6**. There, in addition to the always up-to-date data sheet, you will also find all diagrams and drawings, declarations of conformity, or 2D or 3D models and other necessary materials. For more information, visit www.hakil.com



8590681188903

Application wiring diagram (installation) 1/1

